

CrystalWay CG-S - Exit Sign Luminaires



- Exclusive escape sign panel luminaire with LED technology
- Concise design with highly transparent frame and replaceable inner screen-printed pictograms
- Includes set of pictograms (arrow right, left, down, up, blind) for the most common applications
- Only one order number for wall or ceiling mounting
- Expandable with extensive accessories, e.g. housing for ceiling recessing, wire suspension, pictograms for 90° wall mounting
- Unobtrusive, thin & slim electronic base (Height: only 22mm)
- Optimal recognition via high luminance of white contrast colour > 500 cd/m² according to DIN 4844-1 / ISO 3864-1 (for bright surroundings), and high uniformity L_{min}/L_{max} > 0.8
- Reduced battery costs on account of especially low power consumption
- Low operating costs on account of low effective power of 3.7 W only.
- Minimum maintenance effort and increased safety via use of LEDs with high service life (50,000 hours)
- Shortened inspection effort due to CEWA GUARD Technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditures by STAR Technology

Technical data

Viewing distance	24 m
Luminous flux Φ_E / Φ_{Nenn} at end of rated operating time	100 %
Housing material	Polycarbonat
Housing colour	RAL 9003
Weight	0.7 kg
Type of mounting	Wall and ceiling mounting
Connection terminals	2 x 3 x 2.5 mm ²
Connection voltage	220 - 240 V AC, 50/60 Hz 176 - 275 V DC
Power consumption mains operation (apparent power/effective power)	6.5 VA / 3.7 W
Current consumption - battery operation (220 V)	15 mA
Permissible ambient temperature	-20 °C to +40 °C
Light source	LED strip

Ordering information

40071354593	CrystalWay CG-S	
LUM10560	Wire suspension kit	
LUM10562	Recessed base, for ceiling mounting	
LUM10564	Recessed base with cover, for ceiling mounting	
LUM10566	Concrete box (suitable for recessed base with cover)	
LUM10587	Pictogram - Centre	
LUM10588	Pictogram - Left	
LUM10589	Pictogram - Right	

Wire suspension kit




Recessed base with cover



Dimensions

Wall-surface mounting



Ceiling-surface mounting

