

TITAN 720

Highly efficient LED floodlight designed specifically for high mast and large area lighting.

Electronic, LED control gear driving 96 LEDs at 2.1A with asymmetrical distribution. IP67, Class I protection with 15kA Surge Protection.

Body: recyclable, extruded aluminium and powder-coated steel. Optic Enclosure: PMMA Weather-proof lenses. Reversible mounting bracket supplied, optional spigot adaptors available separately for post-top mounting.



CE LED IP67  

Technical data

Performance

Nominal Flux:	87,000 lm
Net Flux:	80,555 lm
Power Absorption:	705W

Optoelectronics

LED Type:	CREE XP-L
Circuit Board:	MPCB 1.6 mm
CRI:	$70 \leq R \leq 90$
Luminous Eff Loss:	< 1% per annum
Colour Temperature:	3,000 to 5,700K
Lumen Maintenance L90 B10	63,000h
Lumen Maintenance L70 B50	> 100,000h

Optics

Secondary Lens:	Refraction Array
System Treatment:	IP67, Anti-yellowing
Available optics:	FL / FH / SW / SM / ST
No of LEDs / module:	48
No of modules:	2

Luminaire Body

Structure:	Stainless steel
Metal coating:	Powder painted
Heatsinks:	Extruded Aluminium
Bracket:	Central Bolt 20mm
Weight:	32 Kg
Installation height:	15m to 55m
Installation angle:	Tilt Adjustment 330°
Dimensions:	719L x 561W x 245H mm
Windage Area:	0.085 m ²

Electronics

Voltage input:	90-305 VAC 50-60Hz
Active Power F.C.	0.95
Mean time to Failure:	200,000 hrs
Dimming Function:	1-10V
Surge Protection:	15kA, IEEE C62.41.2 Location Category C High
Insulation Class:	IEC Class I
IP Rating:	IP 67
Short Circuit Protection:	Auto-recovery
Over Heat Protection:	Drops output current
Rel. Humidity Range:	0% - 94%
Operating Temp:	-40°C up to +55°C

Normative references

EN 60598-1: 2015 - Luminaires - Part 1: General requirements and tests
 EN 60598-2-5: 2015 Luminaires - Part 2-5: Particular requirements - Floodlights
 EN 62031: 2008 + A2:2015 - LED modules for general lighting - Safety specifications
 EN 60598-2-3: 2003 + A1: 2011 - Luminaires - Part 2-3: Particular requirements - Luminaires for road and street lighting
 EN 62493: 2015 Assessment of lighting equipment related to human exposure to electromagnetic fields
 EN 60529: 1992 + A2: 2013 - Degrees of protection provided by enclosures (IP Code)
 IEC 60068-2-52: 1996 Environmental test - Part 2: Tests - Test Kb - Salt mist cyclic (sodium chloride solutions)
 EN 55015: 2013 + A1: 2015 - Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
 EN 61547: 2009 - Equipment for general lighting purposes - EMC immunity requirements
 EN 61000-3-2: 2014 - Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
 EN 61000-3-3: 2013 - Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
 EN 61643-11: 2012 - Low-voltage surge protective devices. Part 11: Surge protective devices connected to low-voltage power systems - Requirements and test methods
 IEEE C62.41.2-2002 - Recommended practice on characterization of surges in low-voltage AC power



Midstream Lighting Ltd, 1 Chesham Street, London SW1X 8ND, UK
 Tel +44 207 584 8310 Email info@midstreamlighting.com
www.midstreamlighting.com



